



# JMLU2.MH15469 Gaskets and Seals - Component

[Page Bottom](#)

## Gaskets and Seals - Component

[See General Information for Gaskets and Seals - Component](#)

**DIACOM CORP**

MH15469

5 HOWE DR

AMHERST, NH 03031 USA

### Solid Material


Compound Dsg.	Max Svc Temp (°C)	Min Svc Temp (°C)	Hardness Range	Tensile Str (psi)	Elong (%)	Max Comp Set (%)	Max Tensile Set (%)	End Use
<b>Acrylonitrile - Butadiene rubber gasket material</b>								
<b>EE-5504</b>	80	-40	50-60	1545	398	2.9	4.0	F, G, J
<b>EG-5511</b>	60	-40	60-62	1837	475	10.4	1.0	F, J

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

F - Manufactured gas or natural gas

G - Diesel fuel, fuel oil or lubricating oil

J - Liquefied petroleum gas (LP-gas)

Marking: Company name, compound designation and the Recognized Component Mark,  on the material, on a substantial tag, on the container or the smallest packaging.

[Last Updated](#) on 2017-08-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".